



Hand Tool Safety Training



Learning Objectives


- At the end of this session the participant should be able to:
- Identify the hazards associated with various types of hand tools
- 2. Understand the safety best practices that can prevent accidents and injuries when using hand tools
- Know the appropriate personal protective equipment (PPE) that can protect workers against injuries





Introduction

- Hand tools are used by virtually everyone
- Hand tools include anything from axes to wrenches
- Misuse accounts for the majority of accidents and injuries involving hand tools
 - 7 8 percent of all compensable injuries each year in the construction industry
- Improper maintenance is another leading cause of injuries
- Even though the tool is powered by human inertia, these injuries often involve severe disabilities





Common Hand Tool Hazards

- Workers using hand tools may be exposed to a number of potentially serious hazards:
 - Falling objects
 - Objects that fly as a result of contact with tools
 - Objects that are abrasive, or splash
 - Harmful dusts, fumes, mists, vapors, and gases
 - Contact with electrical power sources
- Hazards are usually caused by misuse and improper maintenance



Common Hazards Lead to Serious Injuries

- The following are typical hand tool injuries and some of the probable causes:
 - Loss of eye/vision using a hammer without eye protection
 - Puncture wounds using a screwdriver as a pry-bar
 - Severed fingers, tendons and arteries using a dull knife requires so much force that your hand may slip down the blade.
 - Broken bones using the wrong hammer for the job and smashing a finger.
 - Contusions using a small wrench for a big job and bruising a knuckle.



Using a Hammer Without Eye Protection



Using a Screwdriver as a Pry-Bar



Sledgehammer Crushed Thumb



Hazard Prevention: Inspect Tools Before Use

- All hand tools must be inspected before they are used
- Never use a tool if its handle has splinters, burrs, cracks, splits or if the head of the tool is loose
- Never use impact tools such as hammers, chisels, punches or steel stakes that have mushroomed heads.
- Tag worn, damaged or defective tools "Out of Service" and do not use them









Page 6

Hazard Prevention: Personal Protective Equipment

- PPE must be used whenever a worker <u>could</u> come into contact with a hazard
 - With hand tools in a construction site, that means safety glasses, safety shoes, hard hat and gloves all the time!
 - Most hand tool injuries could be avoided with the proper use of PPE
- PPE is designed for the work being performed use the right equipment!
- PPE must be maintained in good condition, kept clean and properly stored when not in use











Basic Tool Safety Practices

- Safety is a state of mind. Always think when using a tool:
 - Is it in good condition?
 - Is it sized right for the job?
 - Is it in the proper working condition sharp, clean, oiled, dressed and not abused?
- Only use a tool for the job in which it was designed
- Chisels, screwdrivers or other pointed tools should never be carried in clothing pockets
 - Always use tool belts designed for carrying tools
- Never wear sandals, open-toed or canvas shoes when working with tools
- Avoid loose-fitting clothes that might become entangled in a tool
- Always remove rings and other jewelry



NEVER USE A
TOOL FOR A JOB
THAT IT WAS NOT
DESIGNED FOR

Basic Tool Safety Practices, continued

- Make sure your grip and footing are secure when using large tools
- Never carry tools up ladders use a hoist or rope
- Use extra caution when using tools at heights a falling tool can kill a co-worker or customer
- Always pass a tool to another person by the handle never toss it to them
- Select ergonomic tools for your work task when movements are repetitive and forceful





Safety Best Practice - Knives

- Only use a knife with a blade that is fully sharpened
- Always cut in the direction away from your body
- Never use knives that have broken or loose handles
- Never use knives as screwdrivers, pry bars, or can openers
- Never pick up knives by their blades
- Always carry knives with their tips pointed towards the floor
- Never carry knives, scissors or other sharp tools in your pockets unless they are first placed in their sheath or holder
- Never attempt to catch a falling knife
- Store knives in sheaths after using them









Safety Best Practice - Hammers

- Never use a hammer if your hands are oily, greasy or wet
- Always check behind you before swinging a hammer
- Use a claw hammer for pulling nails.
- Never strike nails or other objects with the "cheek" of the hammer
- Do not strike a hardened steel surface, such as a cold chisel, with a claw hammer.
- Never strike one hammer against another hammer
- Never use a hammer as a wedge or a pry bar







Page 11



Safety Best Practice - Screwdrivers

- Never use a screwdriver if your hands are wet, oily or greasy
- Always match the size and type of screwdriver blade to fit the head of the screw
- Do not hold the work piece against your body while using a screwdriver
- Never put your fingers near the blade of the screwdriver when tightening a screw
- Never use a screwdriver to make a starting hole for screws
- Never use a screwdriver as a chisel, pry bar or nail puller
- When performing electrical work, always use an insulated screwdriver
- Never use a screwdriver to test the charge of a battery








Safety Best Practice - Wrenches

- Never use wrenches that are bent, cracked or badly chipped or that have loose or broken handles
- Discard any wrench that has spread or battered jaws, if the handle is bent, or if a wrench has broken or battered points
- Never slip a pipe over a single head wrench handle for increased leverage.
- Never use a shim to make a wrench fit
- Pull on a wrench using a slow, steady pull -- do not use push force on a wrench - losing your balance is more likely if the wrench slips















Safety Best Practice - Pliers

- Never use pliers that are cracked, broken or sprung
- Never use pliers as a wrench or a hammer
- Do not attempt to force pliers by using a hammer on them
- Never slip a pipe over the handles of pliers to increase leverage
- When performing electrical work, always use insulated pliers
- When using the diagonal cutting pliers, shield the loose pieces of cut material from flying into the air by using a cloth or your gloved hand









Safety Best Practice - Snips

- Never use snips as a hammer, screwdriver or pry bar
- Always wear safety glasses or safety goggles when using snips to cut materials
- Always wear your work gloves when cutting materials with snips
- Keep the blade aligned by tightening the nut and bolt on the snips.
- Never use straight cut snips to cut curves
- Always use the locking clip on the snips after you have finished using them - never leave or store snips in the open position









Safety Best Practice - Jacks

- The manufacturer's rated capacity must be marked on all jacks and all jacks must have a stop indicator
 - Never exceed the capacity or the stop indicator
- Jacks should be lubricated and inspected regularly
- When setting up a jack, ensure:
 - The base is centered on a firm, level surface
 - The jack head is placed against a level surface
 - The lift force is applied evenly
- Put a block under the base of the jack when the foundation is not firm
- Place a block between the jack cap and load if the cap might slip
- Immediately block the load after it is lifted







© 2006 RiskAnalytics, LLC

Summary

- Only use a tool for the job in which it was designed
- Always inspect tools before using them
 - Never use tools that are loose or cracked
 - Tag worn, damaged or defective tools "Out of Service" and do not use them
- Always keep tools sharp and in good condition
- After using a tool, clean it and put it back in its proper place
- Always wear PPE that is appropriate for the work
- Never wear loose clothes or jewelry
- Never work with oily or greasy hands
- Remember: You are the key controlling influence that can minimize the hazard!



